## LUCIDUS RED E2G



Perinone			C.I. Solvent Red 179 Colour Index No. 564150		州的水门工		
Technical Ap	plication Data						
		PS	ABS	PC	PET	PA 6	
Heat Stability(C°)		300	300	340	320	320	
Light Fastness SD $rac{1}{3}$ Full Shade		8	7	8	8	7	
Light Fastness SD $\frac{1}{3}$ Reduction		6	6	7	7	7	
Physical and Chemical Characteristics							
Shade				Yellowish red	ł		
CAS No.				89106-94-5			
Density(g/cr	n <sup>3</sup> )			1.44			
Melting poin	t(C°)			260			
Alkali resista	nce			5			
Acid resistan	ce			5			
Range of Ap	plications						
					Spin Dyeing		
PS	• PC	•	PMMA	•	PET	_	
SAN	PET	•	PA 6	•	PA	•	
ABS	• PBT	•	PA 66	•	PAN	_	

## Commentary

Lucidus Red E2G is a yellowish red with very good light fastness and excellent heat resistance, structurally halogen free, suitable for E & E applications.

Note : Data Presented above is based on our present knowledge and is with intentions of providing general guidelines for use of our products. These products are offered by TINTEC without any kind of guarantee. We recommend that customers should test the suitability of these products in their end application before use.